


## 341 Nypel redukujący podwójny sześciokątny gwint zewnętrzny

Wykonanie: odlew ze stali 316 [1.4408]  
lub 304 [1.4308]. EN10241:2000 [DIN2991].  
Gwint BSP wg ISO 7-1R.



d2	d1	L mm *	SW mm *
1/4"	1/8"	31,0/22,5	15,1/15,0
3/8"	1/8"	34,0/24,0	18,6/19,0
	1/4"	34,0/26,5	18,6/19,0
1/2"	1/8"	36,5/27,5	23,0/23,0
	1/4"	36,5/30,0	23,0/23,0
3/4"	3/8"	36,5/30,5	23,0/23,0
	1/8"	40,0/29,0	29,0/29,0
	1/4"	40,0/31,5	29,0/29,0
	3/8"	41,0/32,0	28,5/29,0
1"	1/2"	41,5/35,5	28,5/29,0
	1/4"	41,0/34,5	35,4/36,0
	3/8"	42,5/35,0	35,4/36,0
1 1/4"	1/2"	45,0/38,5	35,4/36,0
	3/4"	45,0/39,5	35,4/36,0
	3/8"	47,0/38,0	44,5/45,0
1 1/2"	1/2"	49,0/41,5	44,5/45,0
	3/4"	49,0/42,5	44,5/45,0
2"	1"	52,0/45,0	44,5/45,0
	1/2"	49,0/41,5	50,0/51,0
	3/4"	49,0/42,5	50,0/51,0
	1"	52,5/45,0	50,0/51,0
2 1/2"	1 1/4"	55,0/47,5	51,0/51,0
	3/4"	41,5/47,5	61,5/63,0
	1"	53,5/50,0	61,5/63,0
	1 1/4"	56,0/52,5	61,5/63,0
3"	1 1/2"	55,5/52,5	61,5/63,0
	1"	63,5/52,0	78,0/80,0
	1 1/4"	63,5/54,5	78,0/80,0
4"	1 1/2"	63,5/54,5	78,0/80,0
	2"	65,5/59,0	78,0/80,0
	1 1/2"	68,0/58,0	92,0/95,0
5"	2"	68,5/62,5	93,0/95,0
	2 1/2"	71,0/64,5	92,0/95,0
	2"	75,0/69,0	117,0/120,0
6"	2 1/2"	75,0/71,0	117,0/120,0
	3"	75,0/74,0	117,0/120,0

Większe wymiary jako 8-kątny